



### Silicon N-Channel Power MOSFET

#### General Description :

HMZ1N65 the silicon N-channel Enhanced VDMOSFET, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is SOT23, which accords with the RoHS standard.

$V_{DSS}$	650	V
$I_D$	0.8	A
$P_D(T_C=25^\circ\text{C})$	2.0	W
$R_{DS(\text{ON})\text{MAX.}}$	13	$\text{m}\Omega$



#### Features :

- Fast Switching
- Low ON Resistance( $R_{dson} \leq 16\Omega$ )
- Low Gate Charge (Typical Data: 6 nC)
- Low Reverse transfer capacitances(Typical: 3.5pF)
- Low  $V_{th}$  (Typical: 1.0V)

#### Applications:

- Power switch circuit of adaptor and charger

#### Absolute ( $T_C=25^\circ\text{C}$ unless otherwise specified ) :

Symbol	Parameter	Rating	Units
$V_{DSS}$	Drain-to-Source Voltage	650	V
$I_D$	Continuous Drain Current	0.8	A
	Continuous Drain Current $T_C=100^\circ\text{C}$	0.6	A
$I_{DM}^{a1}$	Pulsed Drain Current	3.2	A
$V_{GS}$	Gate-to-Source Voltage	$\pm 25$	V
$E_{As}^{a2}$	Single Pulse Avalanche Energy	20	mJ
$E_{Ar}^{a1}$	Avalanche Energy ,Repetitive	6	mJ
$I_{AR}^{a1}$	Avalanche Current	1.1	A
$dv/dt^{a3}$	Peak Diode Recovery $dv/dt$	5.0	V/ns
$P_D$	Power Dissipation	2	W
$T_J, T_{stg}$	Operating Junction and Storage Temperature Range	150, -55 to 150	$^\circ\text{C}$
$T_L$	Maximum Temperature for Soldering	300	$^\circ\text{C}$

Caution Stresses greater than those in the "Absolute Maximum Ratings" may cause permanent damage to the device

### Thermal Characteristics

Symbol	Parameter	Rating	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	62.5	°C/ W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	70	°C/ W

**Electrical Characteristics** (  $T_c = 25^\circ C$  unless otherwise specified ) :

OFF Characteristics						Units	
Symbol	Parameter	Test Conditions	Rating				
			Min.	Typ.	Max.		
$V_{DSS}$	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	650	690	--	V	
$\Delta BV_{DSS}/\Delta T_J$	Bvdss Temperature Coefficient	$I_D=250\mu A$ , Reference $25^\circ C$	--	0.51	--	$V/^\circ C$	
$I_{DS}$	Drain to Source Leakage Current	$V_{DS}=650V, V_{GS}=0V, T_a=25^\circ C$	--	--	1	$\mu A$	
		$V_{DS}=520V, V_{GS}=0V, T_a=125^\circ C$	--	--	100		
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS}=+20V$	--	--	100	nA	
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS}=-20V$	--	--	-100	nA	

ON Characteristics						Units	
Symbol	Parameter	Test Conditions	Rating				
			Min.	Typ.	Max.		
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10V, I_D=0.4A$	--	13.0	16	$\Omega$	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=4.5V, I_D=0.2A$	--	13.5	17	$\Omega$	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=3V, I_D=0.1A$	--	14.5	18	$\Omega$	
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	0.5	--	1.5	V	
$g_{fs}$	Forward Trans conductance	$V_{DS}=15V, I_D=0.8A$	--	0.7	--	S	

Pulse width < 380μs; duty cycle < 2%.

Dynamic Characteristics						Units	
Symbol	Parameter	Test Conditions	Rating				
			Min.	Typ.	Max.		
$C_{iss}$	Input Capacitance	$V_{GS}=0V, V_{DS}=25V$ $f=1.0MHz$	--	120	--	pF	
$C_{oss}$	Output Capacitance		--	12.5	--		
$C_{rss}$	Reverse Transfer Capacitance		--	3.5	--		

Resistive Switching Characteristics						Units	
Symbol	Parameter	Test Conditions	Rating				
			Min.	Typ.	Max.		
$t_{d(ON)}$	Turn-on Delay Time	$I_D=0.8A, V_{DD}=350V$ $V_{GS}=10V, R_g=4.7\Omega$	--	7.3	--	ns	
$t_r$	Rise Time		--	6	--		
$t_{d(OFF)}$	Turn-Off Delay Time		--	21	--		
$t_f$	Fall Time		--	15.5	--		
$Q_g$	Total Gate Charge	$I_D=0.8A, V_{DD}=350V$	--	6.0	--	nC	



HMZ1N65

$Q_{gs}$	Gate to Source Charge	$V_{GS}=10V$	--	0.68	--	
$Q_{gd}$	Gate to Drain ( "Miller" )Charge		--	2.1	--	

**Source-Drain Diode Characteristics**

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$I_{SD}$	Continuous Source Current (Body Diode)		--	--	0.8	A
$I_{SM}$	Maximum Pulsed Current (Body Diode)		--	--	3.2	A
$V_{SD}$	Diode Forward Voltage	$I_S=0.8A, V_{GS}=0V$	--	--	1.5	V
$t_{rr}$	Reverse Recovery Time	$I_S=0.8A, T_j=25^\circ C$	--	374	--	ns
$Q_{rr}$	Reverse Recovery Charge	$dI_F/dt=100A/\mu s, V_{GS}=0V$	--	735	--	$\mu C$

a1 : Repetitive rating; pulse width limited by maximum junction temperature

a2 :  $L=10mH$ ,  $I_D=2A$ , Start  $T_j=25^\circ C$

a3 :  $I_{SD}=0.8A, di/dt \leq 100A/\mu s, V_{DD} \leq BV_{DS}$ , Start  $T_j=25^\circ C$


**Characteristics Curve :**


Figure 1 Maximum Forward Bias Safe Operating Area




Figure 2 Maximum Power Dissipation vs Case Temperature




Figure 3 Maximum Continuous Drain Current vs Case Temperature




Figure 4 Typical Output Characteristics




Figure 5 Maximum Effective Thermal Impedance , Junction to Case




Figure 6 Maximum Peak Current Capability




Figure 7 Typical Transfer Characteristics




Figure 8 Typical Drain to Source ON Resistance vs Gate Voltage and Drain Current




Figure 9 Typical Drain to Source ON Resistance vs Drain Current




Figure 10 Typical Drain to Source on Resistance vs Junction Temperature

