


SCHOTTKY RECTIFIERS

Features:

- Low power loss, high efficiency
- High surge capacity
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Metal silicon junction, majority carrier conduction
- Guard ring for over voltage protection





Absolute Maximum Ratings(Tc=25°C):

| Characteristics | | Symbol | Rating | Unit |
|---|------------------|--------------------|---------|------|
| Maximum Repetitive Reverse Voltage | | V _{RRM} | 200 | V |
| Average Rectified Forward Current | | I _{F(AV)} | 20 | A |
| Non-repetitive Peak Forward Surge Current 8.3ms Single Half-Sine-Wave | | I _{FSM} | 135 | A |
| Collector power dissipation Ta=25°C | P _{tot} | | 2.0 | W |
| Junction temperature | T _j | | 175 | °C |
| Storage temperature range | T _{STG} | | -55~175 | °C |

Electrical Characteristics(Tc=25°C) :

| Characteristics | Symbol | Test Condition | Min | Typ | Max | Unit |
|---------------------------------------|------------------|---|-----|-----|--------------|------|
| Forward Voltage | V _F | I _F =10A; T _c =25°C | | | 0.9 | V |
| Reverse Current | I _R | V _R =200V; T _c =25°C V _R =200V; T _c =125°C | | | 0.01 10.0 | mA |
| Peak Repetitive Reverse Surge Current | I _{RRM} | 2.0 us Pulse Width ,f=1.0KHZ T _J <175°C | | | 3 | A |

| Symbol | Paramter | Typ | Units |
|------------------|------------------|-----|-------|
| R _{θJC} | Junction-to-Case | 1.4 | °C /W |

Package Information**TO-220F PACKAGE**

| | 单位: mm | | |
|-----|--------|------|------|
| | MIN | NOM | MAX |
| A | 4.35 | 4.55 | 4.75 |
| A 1 | 2.3 | 2.5 | 2.7 |
| A 2 | 0.4 | 0.6 | 0.8 |
| A 3 | 2.1 | 2.3 | 2.5 |
| b | 0.6 | 0.8 | 1.0 |
| b 1 | 1.0 | 1.2 | 1.4 |
| c | 0.3 | 0.5 | 0.7 |
| e | 2.3 | 2.5 | 2.7 |
| E | 9.8 | 10 | 10.2 |
| E 1 | 6.3 | 6.5 | 6.7 |
| H | 15.6 | 15.8 | 16.0 |
| H 1 | 8.8 | 9 | 9.2 |
| H 2 | 12.9 | 13.2 | 13.5 |
| H 3 | 3.1 | 3.3 | 3.5 |
| G | 3.1 | 3.3 | 3.5 |
| ΦP | 3.1 | 3.3 | 3.5 |